

PATCH CORD CAT.5E UTP 5E-CCA-UU-24



Technical DATA

Cable Type	U/UTP
Material	CCA
Connector Type	RJ45 (Unshielded)
Color	Grey, Blue, Yellow, Black, Orange, Red.
Max Thickness	0.5 mm
AWG	24 AWG
Standard	Compliant with Cat. 5e requirements of ISO/IEC 11801 ed. 2.2 , Compliant with Cat. 5e requirements of EN 50173, Compliant with Cat. 5e requirements of EN 50168, Compliant with Cat. 5e requirements of TIA 568-A/B, Meet test specifications of TIA 568-B.2-1 With R&M RJ45 connectors in acc. with IEC 60603-7 series, Fulfilled the standard IEC 61935-2:2010

Ordering Details

Part Code	Length In Meters
5E-CCA-UU-24/1	1
5E-CCA-UU-24/2	2
5E-CCA-UU-24/3	3
5E-CCA-UU-24/5	5
5E-CCA-UU-24/10	10
5E-CCA-UU-24/12	12
5E-CCA-UU-24/15	15
5E-CCA-UU-24/20	20
5E-CCA-UU-24/25	25
5E-CCA-UU-24/30	30
5E-CCA-UU-24/40	40
5E-CCA-UU-24/50	50