

## PATCH CORD CAT.6A UTP 6A-Cu-UU-24



### Technical DATA

Cable Type	U/UTP
Material	Copper
Connector Type	RJ45 (Unshielded)
Color	Grey, Blue, Yellow, Black, Orange, Red.
Max Thickness	0.56 mm
AWG	24 AWG
Standard	Compliant with Cat.6a,ISO class E(500MHz) requirements: ISO/IEC 11801 ed.2.2, Compliant with Category 6a,ISO requirements of the standard ISO/IEC 11801 ed.2.2 : June 2011, Compliant with Category 6a, ISO requirement of the standard EN 50173-1: May 2011, Compliant with Category 6a, ISO requirement of the standard TIA 568.C.2, Compliant with Cat.6a ISO component standard IEC 60603-7-51, Fulfilled the standard IEC 61935-2:2010

### Ordering Details

Part Code	Length In Meters
6A-Cu-UU-24/1	1
6A-Cu-UU-24/2	2
6A-Cu-UU-24/3	3
6A-Cu-UU-24/5	5
6A-Cu-UU-24/10	10
6A-Cu-UU-24/12	12
6A-Cu-UU-24/15	15
6A-Cu-UU-24/20	20
6A-Cu-UU-24/25	25
6A-Cu-UU-24/30	30
6A-Cu-UU-24/40	40
6A-Cu-UU-24/50	50